Special care Polish 1

ref 533 10002 ACRYLIC SHEET & BLOCKS

Special care Polish 1 is a mixture of mineral abrasives and saps in aliphatic hydrocarbons with an aromatics content of less than 5%. Special care 1 eliminates slight surface scratches and restores all the original shine and transparency of Altuglas[®].

APPLICATIONS

Special care Polish 1 is designed for components made of Altuglas® sheets: cast and extruded, standard and impact.

It is especially well-suited to the following applications:

- windows
- furniture
- poster advertising panels, display stands
- sanitaryware

PROPERTIES

Colour: Beige Density: 1,048 g/cm³

Viscosity: $150 \pm 50 \text{ MPa} \cdot \text{s}$ at 20°C Dry extract: $\approx 56.4 \text{ %}$, including soaps.

TOXICITY AND SAFETY

Special care Polish 1 has a flash point > 61°C, which makes it inflammable. It is recommended, therefore, that the product be stored away from all sources of ignition.

Special care Polish 1 can react dangerously with highly oxidizing agents, such as strong acids and halogens.

Special care Polish 1 is not subject to any regulations concerning the labelling and transportation of hazardous materials.

STORAGE PRECAUTIONS

Packages must be kept in an area where the temperature is between 0° and 50°C.

Freezing temperatures will damage the product. Kept unopened in its original hermetically-sealed packages at 20°C maximum, Special care Polish 1 is guaranteed to keep for 3 years.

PACKAGING

Special care Polish 1 is delivered in non-divisible cases containing 10 metal tins of 1 liter.

USE OF ALTUGLAS® CLEANER

Special care Polish 1 is chemically inert in relation to Altuglas® and other products in our range.

Prior to polishing cross-sections or grooves, roughness should be minimized with careful sanding. Use a block equipped with "waterproof" abrasive paper. Keep paper damp as you increase grain from n° 600, 800 or 1000 depending on desired surface quality.

The container must be well shaken before every use.

Soak a cotton pad and rub the surface to be polished in a circular motion until the

Special care Polish 1 is completely absorbed.

A chamois cloth can be used to accelerate the operation.

For an optimum quality finish,

use Special care Polish 1 and 2 successively.

Complete the operation by wiping (suede-type soft cloth or cotton pad).

WARRANTY

The information given in this literature is based on the findings of our research and experience.

It is intended as a general guide to the use of our products and must not be considered as a binding specification.

In no way does the information incurs the liability of Altuglas International, especially in case of infringement of the rights of a third party.





